

**Oryx\_ Road Runner\*** Semi-Trailer **Flat Bed 20'-40'-60'**  
Technical Specifications



### Chassis & Shell

---

- **Structure:** Hot-rolled beams with welded ladder type cross-members
- **Axles & Suspension:** mechanical Cantilever Bogie/VB leaf spring type (2x14T/3x12T/3x14T)
- **Brakes:** Two-line air brakes, automatic load sensing valve and ABS/EBS
- **Rims:** 22.5"/20" disc rims
- **Tires:** Size 315/80R22.5" or 12.00R20 **Prime Brand**
- **King Pin:** 2" or 3.5" fixed on sliding plate
- **Landing Gear:** A400 type, 2-speed mechanical, one side operation and suitable base plates
- **Platform:** Made of mild steel ST37.2 / 4mm welded on fortified cross members (Chequered plate)
- **Front Panel:** Fixed type head board with basket for tarpaulin. ST 37.2/2mm
- **Removable stakes** at side and rear
- **Removable grills** on sides and rear with Stowage. (Optional)
- ISO Container twist lock 20' & 40' total 8 nos (optional)
- Ratcheted Rollers both sides (optional)

### Blasting & Painting

---

- Grit blasted to SA2.5, one coat of **Epoxy** primer followed by two coats of **polyurethane**

### Electrical System (ADR compliant)

---

- 24-volts Double- sleeved cabling in rigid tubes
- 7-pin female socket (ISO 1185) S & N type
- Rear Combination lamp
- Side lamps on each side
- Reverse buzzer
- LED Flash Stop lamp

### Accessories

---

- Metallic Mudguards with rubber flaps
- Heavy duty rear bumper
- Spare tyre bracket for two tyres
- Access Ladder
- Two wheel wedges with carriers
- Plastic water tank & Tool Box without tools
- Fire extinguisher box with cylinder
- Lateral protection on both sides

Picture only for reference purpose, specification may differ.

